

C3255

Checkweigher



NTEP CC 04-088

- **Capacity**– 30 lb (15 kg), 60 lb (30 kg), 150 lb (60 kg), 300 lb (150 kg)
- **Stainless Steel Construction**– Wipe-down environment friendly
- **LCD Display**– Bright, large and visible
- **Power Options**– Battery and AC power
- **Preset Targets**– Includes 10 preset
- **Checkweighing Features**– Checkweighing bar graph, push button target setting, simple weight display, over/under/accept indicators, and audible alarm for target
- **Approvals**– NTEP

VALUE IN
WEIGHING

C3255 Checkweigher

Features

Display Type– 7 segment LCD with annunciators and bar graph. Large 1.2" digits.

Battery Operation– Uses 6 “C” cell batteries (not included) allowing remote operation and portability. The battery supports over 120 hours of continuous operation.

Ten Preset Targets– Allows quick selection of the items to be weighed. Setting new targets is quick and simple via the keyboard.

Unit Switching– Accessed through the “mode” key. Either lbs, kg or oz may be selected.

Count Function– A simple and accurate feature is available under the “mode” switch

Target Graph– In the checkweigher mode the graph indicates over, under or accept with a full visual representation of the weight in relation to the target

Folding Column– The display unit folds down for storage and shipping

Selectable Calibration Settings– Choose from full, 1/2, and 1/4 capacity

Key Functions– On/off, mode, net/gross, zero, tare, call, 0-9

Specifications

Capacity / Resolution (NTEP Configurations)

Model	lb	kg
C3255-30	30 x 0.01 lb	15 x 0.005 kg
C3255-60	60 x 0.02 lb	30 x 0.01 kg
C3255-150	150 x 0.05 lb	60 x 0.02 kg
C3255-300	300 x 0.05 lb	150 x 0.02 kg

Scale Dimensions– 19" H x 13.5" W x 19.75" D
483 mm (H) x 343 mm (W) x 502 mm (D)

Platter Size– 13.5" W x 17.4" D
342 mm (W) 442 mm (D)

Operating Temp– 41° F - 95° F (5° C - 35° C)

Power Supply– 15V, 300mA, AC adapter (included)

Packaging Dimensions– 26" L x 20" W x 12" H
660 mm (L) x 508 mm (W) x 305 mm (H)

Shipping Weight– 33 lb (15 kg)

Certifications–

NTEP CC# 04-088 (3,000 divisions)

Non NTEP (6,000 divisions)

Full FCC compliance

UL/CUL power adapter



Model C3255 Battery Compartment



a division of Avery Weigh-Tronix, LLC

Salter Brecknell Weighing Products

1000 Armstrong Dr., Fairmont, MN 56031
Toll free: 800-637-0529, Tel: 507-238-8702
Fax: 507-238-8271
e-mail: sales@salterbrecknell.com
www.salterbrecknell.com

